



# **Residential Elevator Design Guide (Hydraulic)**

**ASME 17.1A - 2022 CSA B44:22**

**All Models - Elmira, Heritage & Cambrian**

## Table of Contents

---

|                                                          |       |
|----------------------------------------------------------|-------|
| Introduction                                             | 3     |
| Planning for a Cambridge Elevating Home Elevator         | 3     |
| Provisions by Others                                     | 4     |
| Description of Elevator Equipment                        | 5     |
| Hoistway Construction – General Notes                    | 6     |
| Hoistway Construction – Wood Stud Wall                   | 7     |
| Hoistway Elevation – Overhead Requirements               | 8     |
| Pit Details                                              | 9     |
| Machine Room Details – General Layout                    | 10    |
| Machine Room Details – Controller / Pump Details         | 11    |
| Machine Room-Less Details - General Layout               | 12    |
| Cambrian Landing Frame Details - Elevation               | 13    |
| Cambrian Landing Frame Details - Layout                  | 14    |
| Drawings - Elmira Model Cab/Hoistway Size Layout         | 15-17 |
| Drawings - Heritage Model Cab/Hoistway Size Layout       | 18    |
| Drawings - Cambrian Model Cab/Hoistway Size Layout       | 19    |
| Elevator Specifications for ASME A17.1 Part V Compliance | 20-22 |

## Introduction

This design guide assists architects, builders, contractors, home owners and elevator professionals in planning for a home elevator installation that meets the requirements of ASME A17.1-2022 Part V/CSA B44:22.

Please note this guide provides nominal dimensions and specifications and is useful for initial planning. Before starting construction please consult the specific application drawings provided by Cambridge Elevating that indicate exact dimensions for your project.

Please note that due to product enhancements and continually evolving codes, the information in this guide is subject to change without notice.

## Planning for a Cambridge Elevating Home Elevator

The following planning procedure is strongly recommended:

1. Determine the customer's intended use.
2. Determine the customer's desired convenience level with respect to model type:
  - Elmira – swing landing door with manual (or automatic) accordion cab gate
  - Heritage – swing landing door with automatic sliding cab door panels
  - Cambrian – automatic sliding door panels on cab and each landing
3. Determine local, state and national code requirements of site.
4. Use pages 6 through 9 for hoistway construction, pit depth and overhead clearance requirements.
5. Use pages 10 and 11 to plan for a machine room and electrical requirements.
6. Use page 15 through 19 to determine car and hoistway size requirements.
7. Use page 13 and 14 to plan for the Cambrian model's sliding landing frames.

## Provisions By Others

- Provide one permanent 220/1/60 (30 amps) & one 110/1/60 (15 amps) power source to the designated machine room location. Both electrical disconnects are provided by the elevator manufacturer.
- Provide appropriate sleeves for both the electrical conduit and hydraulic line from the drive unit to the hoistway. Trenching may be required if the machine room is not adjacent to hoistway.
- Provide an enclosed, plumb and square hoistway with smooth interior surfaces, as per elevator manufacturer's engineered drawings. Include for fascias or furring of hoistway interior. To be inspected and confirmed by elevator contractor prior to elevator installation.
- Provide required overhead clearance based on engineered drawings.
- Provide floor finishes inside elevator cab.
- Suitable lintels over landing entrances are to be provided for Cambrian model only – per Cambrian Landing Frame Details, see page 12.
- Provide required rough openings at each hoistway landing as per elevator manufacturer's engineered drawings.
- Provide sufficient machine-room area suitable to contain hydraulic power unit and elevator controller & disconnect based on elevator manufacturer's engineered drawings.
- Provide telephone connection to outside line for integration into elevator controller.
- Provide required pit depth and size as per elevator manufacturer's engineered drawings.
- Provide substantial level pit floor slab to support loads indicated on elevator manufacturer's engineered drawings.
- Provide required structural support for guide rail fastenings as per elevator manufacturer's engineered drawings.
- Install rail bracket inserts (Supplied by CE) into concrete rail support wall during construction per elevator manufacturer's engineered drawings, only if required.
- Provide required building permit(s) and/or engineering services as per local authorities.
- Provide pit water proofing or sump pump, only if required.
- Provide all finishes around landing door frames and landing entrances.

## Description of Elevator Equipment

### General

- Rated load: Up to 1,500 lbs. where permitted by local codes
- Nominal speed: 40 feet per minute
- *Elmira* minimum pit depth: 8"
- *Elmira* minimum overhead clearance: 96"
- *Heritage/Cambrian* minimum pit depth: 12"
- *Heritage/Cambrian* minimum overhead: 108"
- Maximum travel: 50 feet
- Maximum number of stops: 6

### Mechanical Equipment

- 220 VAC, 60 Hz, 30 Amp single phase power
- Dual 8 lb. modular T-rail system
- Two 3/8" diameter, 17 x 9 wire ropes
- Sling assembly
- Forged rope sockets
- 2:1 roped hydraulic single stage cylinder
- Submersed electric motor with 2-speed adjustable valve system

### Cab and Appointments

- Car size: Up to 20 sq. ft. standard
- Cab height: 84" standard, 96" & custom optional
- Recessed LED cab lights – 2 or 4 lights depending on cab size + 6 lights pin lights
- Interior cab walls and ceiling finish, choice of:  
Melamine: alabaster, gibraltar, maple, palomino, walnut, white  
Veneer (unfinished) –birch, cherry, maple, oak, walnut  
(MDF) Medium density fibreboard – paint grade
- Rough plywood cab floor with 3/4" recess

### Gates and Doors

- ***Elmira***  
Swing door for each landing  
Horizontally collapsible accordion style car gate(s)
- ***Heritage***  
Swing door for each landing  
Automatic sliding cab door panels (beige or s/s)
- ***Cambrian***  
Automatic sliding cab door panels (beige or s/s)  
Automatic sliding landing door panels (beige or s/s)

### Controls

- Microprocessor controller with relays for basic operation
- Fully automatic operation
- Automatic timed cab lighting
- Stainless steel car operating panel (COP), telephone box and hall call stations
- Dual illuminated hall call station push buttons and position indicating push buttons on COP
- Emergency stop switch on COP
- LED/dot matrix Digital Position Indicator (DPI) in car

### Safety Devices

- Stainless steel handrail inside cab
- 220 VAC lockable disconnect for power unit
- Final limit switch
- Slack rope safety switch
- Pit stop switch
- Car top stop switch
- Line rupture valve
- Low pressure switch
- Automatic leveling (anti-creep)
- Emergency battery lowering
- Electro-mechanical door interlocks
- Manual lowering device
- Telephone in cab

### Options

- Custom cab sizes/heights. Oversized cabs where permitted (variance may be required)
- Custom finish elevator fixtures (COP, telephone box and hall call stations) Consult Cambridge Elevating for options.
- Two piece hydraulic jack
- Additional handrails in cab
- LED/dot matrix Digital Position Indicator (DPI) hall call stations on landings
- Veneer wrapped sliding door panels (Heritage/Cambrian)

## Hoistway Construction – General Notes

- A load-bearing wall is required to sustain rail reactions; please see *Rail Wall Construction – Wood Stud Wall (next page)* for detail.
- Hoistway must be in accordance with ASME A17.1-2022/CSA B44:22, **AND** all local codes and regulations.
- Pit floor construction must withstand a 5,500 lb. load.
- Due to limited clearances, it is necessary that hoistway walls be square and plumb. Maximum permissible deviation from hoistway top to bottom is 1/8".
- Building structure must sustain a chain hoist for hoisting elevator materials to the top of the hoistway during installation.
- A structural engineer must ensure that building and hoistway can safely support all loads imposed by the elevator equipment.
- The drawings contained herein have been prepared using engineering principles and the design loads that are applied by the rails to the wall. However the details and member sizes and the attachments to the structure should not be construed as a complete wall system. The contractor and/or the project engineer are responsible to evaluate the other loads that are applied to the wall from the floor or roof system and modify sizes or connections as required by their analysis.

RAIL WALL SHEATHING  
**3/4" PLYWOOD**  
 SCREWED TO STUDS **EVERY 12"**  
**WITH #10-2-1/2" SCREWS MINIMUM**


FOR BEST RESULTS **USE A CONSTRUCTION ADHESIVE** IN ADDITION TO REQUIRED WOOD SCREWS

WALLS WITH **DOOR OPENINGS MUST HAVE 2"X4" CONSTRUCTION**

ALL OTHER WALLS  
 AS PER LOCAL  
 BUILDING CODE

SURFACE OF PLYWOOD  
**FLUSH WITH WALL OF PIT**

BOTTOM FLOOR  
 SLAB



RAIL CENTERLINE  
 AS PER PROJECT  
 SHOP DRAWINGS

MIDDLE STUDS  
 THREE 2" x 6"

16 1/4" 16 1/4"


- CHANNEL CONSTRUCTION TYPICAL **TWO PLACES**
- TWO 2" x 12" INSIDE TWO 2" x 6"
- 2x6s **SCREWED TO 2x12s EVERY 6"**  
**WITH #10x3-1/2" WOOD SCREWS**
- CHANNELS AND MIDDLE STUDS  
 BETWEEN FLOORS **FULL HEIGHT OF HOISTWAY**

RAIL WALL CHANNEL  
 ASSEMBLY

TOP VIEW

DOOR  
 WALL

3/4"  
 PLYWOOD



CAMBRIDGE ELEVATING IS NOT RESPONSIBLE FOR THE STRUCTURAL DESIGN OF THE BUILDING AND ITS ABILITY TO SUPPORT THE ELEVATOR LOADS AND/OR REACTIONS


THIS DRAWING AND THE INFORMATION IT CONTAINS ARE PROPRIETARY TO CAMBRIDGE ELEVATING INC. THIS DOCUMENT MUST NOT BE DUPLICATED, OR ITS CONTENTS USED OR DISCLOSED (IN WHOLE OR IN PART) WITHOUT THE WRITTEN PERMISSION FROM CAMBRIDGE ELEVATING INC.

**CAMBRIDGE**  
 ELEVATING

181 SHEARSON CRES  
 CAMBRIDGE, ONTARIO  
[WWW.CAMBRIDGEELEVATING.COM](http://WWW.CAMBRIDGEELEVATING.COM)

HERITAGE/CAMBRIAN  
STANDARD HEIGHT DOORS  
78.75" [2000mm] HIGH

ELMIRA



CAMBRIDGE




ELEVATING

181 SHEARSON CRES

CAMBRIDGE, ONTARIO

WWW.CAMBRIDGEELEVATING.COM

THIS DRAWING AND THE INFORMATION IT CONTAINS ARE PROPRIETARY TO CAMBRIDGE ELEVATING INC. THIS DOCUMENT MUST NOT BE DUPLICATED, OR ITS CONTENTS USED OR DISCLOSED (IN WHOLE OR IN PART) WITHOUT THE WRITTEN PERMISSION FROM CAMBRIDGE ELEVATING INC.



PIT FLOOR TO BE DESIGNED FOR AN IMPACT LOAD OF 9600LBS  
AND A STATIC LOAD OF 5500LBS UNDER CYLINDER

REINFORCING AND STRENGTH AS PER LOCAL  
STANDARDS AND CODES

## RESIDENTIAL PIT DETAILS


**CAMBRIDGE**  
E L E V A T I N G

181 SHEARSON CRES  
CAMBRIDGE, ONTARIO  
WWW.CAMBRIDGEELEVATING.COM







THIS DRAWING AND THE INFORMATION IT CONTAINS ARE PROPRIETARY TO  
CAMBRIDGE ELEVATING INC. THIS DOCUMENT MUST NOT BE DUPLICATED,  
OR ITS CONTENTS USED OR DISCLOSED (IN WHOLE OR IN PART) WITHOUT  
THE WRITTEN PERMISSION FROM CAMBRIDGE ELEVATING INC.

## Machine Room Details – General Layout

- Machine room must be in accordance with all codes and regulations.
- A 220 VAC, 60 Hz, 30 Amp single phase power source in the machine room to be provided.
- A 115 VAC, 60 Hz, 15 Amp single phase power source in the machine room to be provided.
- A telephone line circuit to be provided if required. This circuit must be connected to an outside line.



TYPICAL RESIDENTIAL MACHINE ROOM  
MAY NOT BE REQUIRED



### WIRE GAUGE AS PER LOCAL CODE REQUIREMENTS

USUALLY MOUNTED IN  
MECHANICAL ROOM  
ON WALL WITHIN 6' OF  
HYDRAULIC POWER UNIT  
OR TO STRUTS MOUNTED  
ON REAR OF PUMP TANK

### BES4 RESIDENTIAL PUMP CONTROLLER DETAILS

# CAMBRIDGE


E L E V A T I N G

181 SHEARSON CRES  
CAMBRIDGE, ONTARIO  
WWW.CAMBRIDGEELEVATING.COM

THIS DRAWING AND THE INFORMATION IT CONTAINS ARE PROPRIETARY TO  
CAMBRIDGE ELEVATING INC. THIS DOCUMENT MUST NOT BE DUPLICATED,  
OR ITS CONTENTS USED OR DISCLOSED (IN WHOLE OR IN PART) WITHOUT  
THE WRITTEN PERMISSION FROM CAMBRIDGE ELEVATING INC.



## Machine Room-Less (MRL) General Layout

- Machine room must be in accordance with all codes and regulations.
- A 220 VAC, 60 Hz, 30 Amp single phase power source in the machine room to be provided.
- A 115 VAC, 60 Hz, 15 Amp single phase power source in the machine room to be provided.
- A telephone line circuit to be provided if required. This circuit must be connected to an outside line.




### Sample Controller Position Measurement Guide

- Limit of 55' of wire between pump and controller
- Measurements below are for illustration only, controller location will differ for each job
- Controller elevation (floor) and wall distance to hoistway is required before job can be approved





## Cambrian Landing Frame Details – Elevation

- It is the recommendation of Cambridge Elevating to leave door walls wide open for installation.
- Landing door jambs and header fit within rough stud opening. Landing door operating mechanism, door frames and sill hang in hoistway attached to inside wall of hoistway using brackets.
- Drawing below depicts view from landing looking into elevator hoistway (rails support on right wall).




## Cambrian Landing Frame Details – Layout

- It is the recommendation of Cambridge Elevating to leave door walls wide open for installation.



## Elmira Model Cab / Hoistway Size Layout



**TYPE 1 - INLINE**

### Machine Room Required

| Cab Size  | Hoistway Size<br>Width x Depth | Centerlines  |           |
|-----------|--------------------------------|--------------|-----------|
|           |                                | Landing Door | Rail Wall |
| 36" x 48" | 54" x 53.75"                   | 31"          | 27.25"    |
| 36" x 54" | 54" x 59.75"                   | 31"          | 27.75"    |
| 36" x 60" | 54" x 65.75"                   | 31"          | 30.75"    |
| 40" x 48" | 58" x 53.75"                   | 35"          | 27.25"    |
| 40" x 54" | 58" x 59.75"                   | 35"          | 27.75"    |


Please note dimensions remain for mirrored configurations.

### Machine Room-Less (MRL)


| Cab Size  | Hoistway Size<br>Width x Depth | Centerlines  |                  |
|-----------|--------------------------------|--------------|------------------|
|           |                                | Landing Door | Rail Wall        |
| 34" x 54" | 53.5" x 59.75"                 | 32.5"        | 26.875" <b>M</b> |
| 40" x 54" | 59.5" x 59.75"                 | 36.5"        | 26.875" <b>M</b> |
| 48" x 60" | 67.5" x 65.75"                 | 44.5"        | 29.875"          |

**M - Represents Mini Sling Rail Wall Backing**

## Elmira Model Cab / Hoistway Size Layout



**TYPE 2 - THROUGH**



**TYPE 5 - INLINE**

### Machine Room Required

| Cab Size  | Hoistway Size<br>Width x Depth | Centerlines  |           |
|-----------|--------------------------------|--------------|-----------|
|           |                                | Landing Door | Rail Wall |
| 36" x 48" | 54" x 50.5"                    | 31"          | 25.25"    |
| 36" x 54" | 54" x 56.5"                    | 31"          | 27.25"    |
| 36" x 60" | 54" x 62.5"                    | 31"          | 31.25"    |
| 40" x 48" | 58" x 50.5"                    | 35"          | 24.25"    |
| 40" x 54" | 58" x 56.5"                    | 35"          | 27.25"    |

### Machine Room Required


| Cab Size  | Hoistway Size<br>Width x Depth | Centerlines  |           |
|-----------|--------------------------------|--------------|-----------|
|           |                                | Landing Door | Rail Wall |
| 44" x 42" | 54" x 57.25"                   | 31"          | 27"       |
| 48" x 42" | 58" x 57.25"                   | 35"          | 29"       |
| 54" x 48" | 64" x 63.25"                   | 41"          | 32"       |
| 60" x 48" | 70" x 63.25"                   | 47"          | 35"       |

Please note dimensions remain for mirrored configurations.

### Machine Room-Less (MRL)

| Cab Size  | Hoistway Size<br>Width x Depth | Centerlines  |           |
|-----------|--------------------------------|--------------|-----------|
|           |                                | Landing Door | Rail Wall |
| 48" x 42" | 61" x 57.25"                   | 35"          | 26.5"     |
| 54" x 44" | 64.5" x 59.25"                 | 41"          | 30"       |
| 60" x 48" | 70.5" x 63.25"                 | 47"          | 35"       |

## Elmira Model Cab / Hoistway Size Layout



**TYPE 3 or 4 (90-DEGREE) LH or RH**

### Machine Room Required

| Cab Size  | Hoistway Size<br>Width x Depth | Centerlines  |           |
|-----------|--------------------------------|--------------|-----------|
|           |                                | Landing Door | Rail Wall |
| 36" x 48" | 51.25" x 53.75"                | 28.5"        | 27.75"    |
| 40" x 60" | 55.25" x 65.75"                | 32.5"        | 30.75"    |
| 48" x 48" | 63.25" x 53.75"                | 40.5"        | 24.75"    |
| 48" x 60" | 63.25" x 65.75"                | 40.5"        | 30.75"    |


Please note dimensions remain for mirrored configurations.

### Machine Room-Less (MRL)

| Cab Size  | Hoistway Size<br>Width x Depth | Centerlines  |                  |
|-----------|--------------------------------|--------------|------------------|
|           |                                | Landing Door | Rail Wall        |
| 36" x 54" | 51.25" x 59.75"                | 30.5"        | 26.875" <b>M</b> |
| 40" x 60" | 55.25" x 65.75"                | 32.5"        | 29.875"          |
| 48" x 60" | 63.25" x 65.75"                | 40.5"        | 29.875"          |

**M - Represents Mini Sling Rail Wall Backing**

## Heritage Model Cab / Hoistway Size Layout



**TYPE 1 - INLINE**

### Machine Room Required


| Cab Size                     | Hoistway Size<br>Width x Depth | Centerlines  |           |
|------------------------------|--------------------------------|--------------|-----------|
|                              |                                | Landing Door | Rail Wall |
| 44" x 48"<br>(2 panel doors) | 62" x 57.75"                   | 38.75"       | 27.75"    |
| 36" x 48"<br>(3 panel doors) | 54" x 58.375"                  | 32.75"       | 28"       |
| 36" x 60"<br>(3 panel doors) | 54" x 70.375"                  | 32.75"       | 34"       |
| 40" x 54"<br>(3 panel doors) | 58" x 64.375"                  | 34.75"       | 31"       |

Please note dimensions remain for mirrored configurations.

### Machine Room-Less (MRL)

|          | Cab Size  | Hoistway Size<br>Width x Depth | Centerlines  |              |
|----------|-----------|--------------------------------|--------------|--------------|
|          |           |                                | Landing Door | Rail Wall    |
| 32" Door | 36" x 48" | 55.5" x 58.375"                | 34.25"       | 26" <b>M</b> |
| 36" Door | 40" x 54" | 59.5" x 64.375"                | 36.25"       | 30"          |
| 36" Door | 48" x 60" | 67.5" x 69.25"                 | 44.25"       | 32.25"       |

**M - Represents Mini Sling Rail Wall Backing**




**TYPE 2 - THROUGH**

### Machine Room Required

| Cab Size                     | Hoistway Size<br>Width x Depth | Centerlines  |           |
|------------------------------|--------------------------------|--------------|-----------|
|                              |                                | Landing Door | Rail Wall |
| 44" x 48"<br>(2 panel doors) | 62" x 57.5"                    | 38.75"       | 28.75"    |
| 36" x 48"<br>(3 panel doors) | 54" x 58.75"                   | 32.75"       | 29.375"   |
| 36" x 60"<br>(3 panel doors) | 54" x 70.75"                   | 32.75"       | 35.375"   |
| 40" x 54"<br>(3 panel doors) | 58" x 64.75"                   | 34.75"       | 32.375"   |

Please note dimensions remain for mirrored configurations.

## Cambrian Model Cab / Hoistway Size Layout




**TYPE 1 – INLINE**

32" Door

36" Door

36" Door



**TYPE 2 – THROUGH**

### Machine Room Required

| Cab Size                     | Hoistway Size<br>Width x Depth | Centerlines  |           |
|------------------------------|--------------------------------|--------------|-----------|
|                              |                                | Landing Door | Rail Wall |
| 44" x 48"<br>(2 panel doors) | 62" x 61.75"                   | 38.75"       | 31.75"    |
| 36" x 48"<br>(3 panel doors) | 54" x 63.25"                   | 32.75"       | 33"       |
| 36" x 60"<br>(3 panel doors) | 54" x 75.25"                   | 32.75"       | 39"       |
| 40" x 54"<br>(3 panel doors) | 58" x 69.25"                   | 34.75"       | 36"       |

Please note dimensions remain for mirrored configurations.

### Machine Room-Less (MRL)

| Cab Size  | Hoistway Size<br>Width x Depth | Centerlines  |                |
|-----------|--------------------------------|--------------|----------------|
|           |                                | Landing Door | Rail Wall      |
| 36" x 48" | 55.5" x 63.25"                 | 34.25"       | 30.5" <b>M</b> |
| 40" x 54" | 59.5" x 69.25"                 | 36.25"       | 34.625"        |
| 48" x 60" | 67.5" x 73.75"                 | 44.25"       | 37.5"          |

**M - Represents Mini Sling Rail Wall Backing**

### Machine Room Required

| Cab Size                     | Hoistway Size<br>Width x Depth | Centerlines  |           |
|------------------------------|--------------------------------|--------------|-----------|
|                              |                                | Landing Door | Rail Wall |
| 44" x 48"<br>(2 panel doors) | 62" x 66.5"                    | 38.75"       | 33.75"    |
| 36" x 48"<br>(3 panel doors) | 54" x 68.5"                    | 32.75"       | 34.25"    |
| 36" x 60"<br>(3 panel doors) | 54" x 80.5"                    | 32.75"       | 40.25"    |
| 40" x 54"<br>(3 panel doors) | 58" x 74.5"                    | 34.75"       | 37.25"    |

Please note dimensions remain for mirrored configurations.

# Cambridge Elevating Inc. Residential Elevator Specifications

## PART 1 – GENERAL

### 1.1 Summary

This specification describes the planning, labor, and materials required to install a private residence home elevator manufactured by Cambridge Elevating Inc.

### 1.2 System Description

A private residence 1:2 roped hydraulic elevator complete with guide rail system, hydraulic power unit, control panel, switches, wiring and any parts necessary to properly install the elevator to meet performance, safety and code standards.

### 1.3 Quality Assurance

The elevator shall be designed, tested and installed in compliance with all applicable regulations and in accordance with ASME A17.1/CSA B44.0 standards. Elevator may be subject to state, local and city approval prior to installation and subject to inspection after installation.

### 1.4 Applicable Codes and Standards

- 1.4.1 ASME A17.1/CSA B44:22, Section 5.3 *Private Residence Elevators*
- 1.4.2 ASME A17.5/CSA B44.1, *Elevator and Escalator Electrical Equipment*
- 1.4.3 ICC/ANSI A117.1-1998, *Accessible and Usable Buildings and Facilities*
- 1.4.4 NFPA 70-1999, *National Electric Code*
- 1.4.5 ADAAG, *Americans with Disabilities Act Accessibility Guidelines*

## PART 2 – PREPARATORY WORK BY OTHERS

### 2.1 Hoistway

Provide an enclosed, plumb and square hoistway with smooth interior surfaces. Provide fascias or furring of hoistway interior where required. Provide correct door RSO and headers as described on site specific layout drawings. Construction of hoistway, including rail support wall and pit floor must withstand all loads as described on site specific layout drawings. Rail wall construction must provide adequate anchoring means for guide rail support system as described in hoistway detail drawings.

### 2.2 Machine Room

Provide a machine room as required by applicable codes and standards.

### 2.3 Electrical

2.3.1 General Contractor to provide one 220 VAC, 60 Hz, 30 Amp single phase power source in the machine room. 230 VAC disconnect provided by Cambridge Elevating.

2.3.2 General Contractor to provide one 120VAC, 60 Hz, 15 Amp power source and disconnect in the machine room. 120 VAC disconnect provided by Cambridge Elevating.

## PART 3 – SUBMITALS

### 3.1 Approval Drawings

Approval drawings shall show a complete layout of elevator equipment, including plan and elevation views.

## **PART 4 – PRODUCT**

### **4.1 Equipment Manufacturer**

The elevator shall be manufactured by Cambridge Elevating Inc.

### **4.2 Components**

The elevator will have the following components.

#### **4.2.1 Cab**

4.2.1.1 Car sizes **(please visit our full drawings pages at (<http://cambridgeelevating.com/technical-documents>)**

**Please refer to the Drawings pages for representative standard sizes.** Custom cab sizes are available, please consult your authorized dealer or CE sales representative.

**\*\* A minimum cab width of 44" is required for 2-speed/panel doors.**

#### **4.2.1.2 Cab Configuration**

Inline (enter/exit same side), 90 degree or straight-thru layouts available.

#### **4.2.1.3 Cab Construction**

Metal bracket and/or tubular frame structure with melamine, veneer, stainless steel or laminate finish panels. Ceiling white melamine or to match walls. Rough plywood floor is supplied - finish flooring by others.

#### **4.2.1.4 Car Operating Panel**

A brushed stainless steel flush panel is built into the cab wall. Floor selection pushbuttons with a dual color LED floor number and annular ring. Alarm button, emergency stop button, emergency light and integral phone box with phone and hinged cover are included.

#### **4.2.1.5 Hand Rail**

Brushed stainless steel handrail mounted to cab wall (shipped loose in unfinished cabs) in solid flat bar or cylindrical. (Standard handrail is 36" x 1½" straight ends, flat)

### **4.2.2 Hydraulic Power Unit and Motor**

Power unit to consist of 20 U.S. gallon enclosed metal tank, 4.0hp or 5.0hp submersible induction motor and pump. Two-speed valve complete with adjustable leveling, pressure relief valve and shut off ball valve. Pressure gauge, manual lowering valve and overheat thermistor included. Tank heater option is available.

### **4.2.3 Controller**

Certified relay controller utilizing a Machine Control Unit (MCU) to manage the flow of signal information. Battery back-up to allow lowering of car and unlocking and opening of doors during power outages.

### **4.2.4 Cylinder**

Single stage jack with line rupture valve, 750 psi working pressure

#### **4.2.5 Ropes**

Two 3/8" diameter, 9 x 17 wire ropes.

#### **4.2.6 Guide rail**

Dual 8 lb. steel modular T-rail system.

#### **4.2.7 Car Sling**

The elevator cab shall be supported by the car sling. The car sling shall be made of structural and formed steel and equipped with guide rollers and Type "A" roller safeties complete with slack rope safety switch.

#### **4.2.8 Gates and Doors**

Landings: Automatic horizontally sliding two or three speed side opening beige epoxy or brushed stainless door panels complete with matching frame and sill OR Manual swing door on landing provided by General Contractor, the electromechanical door interlock can be provided by CEI (Automatic door operator available).

Cab Door/Gate: Automatic horizontally sliding two or three speed side opening beige epoxy or brushed stainless panels complete with sill OR horizontally sliding collapsible accordion style car gate (various finishes available).

#### **4.2.9 Safety Devices**

The elevator will have the following safety devices:

- 4.2.9.1 208/230 VAC lockable disconnect for power unit
- 4.2.9.2 Final limit
- 4.2.9.3 Slack rope safety switch
- 4.2.9.4 Pit stop switch
- 4.2.9.5 Car top stop switch
- 4.2.9.6 Line rupture valve
- 4.2.9.7 Low pressure switch
- 4.2.9.8 Automatic re-leveling
- 4.2.9.9 Emergency battery lowering
- 4.2.9.10 Electro-mechanical door interlocks
- 4.2.9.11 Manual lowering device
- 4.2.9.12 Handrail inside cab
- 4.2.9.13 Emergency lighting in cab
- 4.2.9.14 Phone in cab

### **PART 5 – EXECUTION**

#### **5.1 Examination**

All site dimensions and conditions shall be verified to ensure they meet specifications, codes and regulations.

#### **5.2 Installation**

Confirm that all site dimensions and conditions match those specified on shop drawings. Do not proceed with installation if the site dimensions and conditions are not acceptable. Elevator shall be installed by trained technicians in accordance with approved plans, specifications, manufacturer's installation instructions and local codes.

#### **5.3 Maintenance**

Elevator shall be maintained in accordance with the manufacturer's instructions and all applicable codes.

#### **5.4 Warranty**

Elevator shall carry a thirty-six (36) month limited warranty on parts only.

[www.CambridgeElevating.com](http://www.CambridgeElevating.com)